

Typ: JDW-10

Art.-No.: H530997

Features:

Differential pressure switch, mechanical, 400...1600Pa, monitor, , Toggler, 12-230 VAC, 1,5(0,4)AAC, 12-24 VDC, 1(0,2)ADC, hysteresis 30...60Pa

Application:

Monitoring of overpressure, differential or under-pressure of air and incombustible, non-aggressive gases. Exhaust or fan monitoring or flow monitor for securing electrical heat registers, as filter monitoring, air pressure shortage safeguard, limit value controller.

JDW-...: Supplied without mounting bracket, can be screwed on directly (with 2 screws).

JDW-...Z: Supplied with attached mounting bracket JZ-10.

JDL-...: Supplied with attached mounting bracket JZ-10.

Note: Once the differential pressure switch has connected a voltage > 24 V and a current > 0,1 A, the gold layer at the contacts will have burnt away. Thereafter, the differential pressure switch can only be operated at this or a higher power.

Note: The hose set is not a part of the delivery scope and must be ordered separately.

Technical Data:

Dimensions of housing:	86 x 46,5 x 90 mm
Number of outputs:	2
Number, control range:	1
Output signal:	switching
Output signal:	switching
Rated impulse voltage:	4000 V
Operating voltage:	none
Pressure:	yes
Pressure connection:	6,2 mm
setting range to:	1600
setting range:	all data in Pa
setting range from:	400
Electrical connection:	Screw-type terminals
Colour of housing:	black
Sensor:	Pressure membrane
Function type:	Monitors
Hysteresis:	approx. 30...60 Pa depending on the setting range

Internal setting:	yes
Storage temperature:	-15...+80 °C
Scope of supply:	Differential pressure switch
Material of housing:	Plastic
max. pressure:	5000 Pa
max. sensor temperature:	80
max. switching voltage:	230 VAC, 50 Hz 24 VDC
max. switching current:	1,5 (0,4) AAC 1 (0,2) ADC
Medium:	Air, not aggressive
min. switching voltage:	12 VAC, 50 Hz 12 VDC
min. switching current:	1 mA
Installation/fastening:	Wall mounting
Surface quality:	matt
potential-free:	yes
Control range up to:	1600
Control range from:	400
Control function:	switches if the pressure is undershot or overshoot
Switching element:	Microswitch
Switching contact:	Toggler, gold contact
Switching power:	345 WAC, 24 WDC
Degree of protection:	IP 54
Protection class:	II
Safety and EMC:	according to DIN EN 60730
Set point adjuster:	yes
Ambient temperature up to:	80
Ambient temperature from:	-15
Degree of fouling:	II
Accessories:	connection set: JZ-06/1, installation bracket: JZ-10
permissible medium temperature:	-15...+80°C
Permissible atmospheric humidity:	max. 95% r.h., non-condensing

Circuit Diagram:

